

“The Admiral Pro” 32ch NVR v5 - ADMP32P24-V5

32 channel AI NVR with 24 built in PoE ports and Dual LAN



- Supports up to 32 cameras
- 24 Built in PoE Ports
- Dual LAN Functionality
- NDAA Compliant
- 384Mbps Incoming Bitrate
- 24 Built in Plug and Play PoE ports
- Extended transmission PoE ports
- Two Independent HDMI Outputs
- TraceSearch **or** Ultra Motion/Smart Intrusion Mode
- Up to 16 UMD or 8 Smart Intrusion by NVR
- Plugin-free web support
- RAID 1&5 Support
- 3 Year Warranty Standard
- 5 Year Warranty Option



Updated 1/2026

For More Information Contact SCW

Toll Free: 828-483-4237 • Fax 1.866.337.9542

Email: hello@GetSCW.com

www.getscw.com

Main Specs	
Video Input	Up to 32 IP Cameras
Total Bitrate	384Mbps Incoming (200Mbps Smart Mode On) 384Mbps Outgoing (200Mbps Smart Mode On)
Recording Resolution	Up to 32MP
Video Compression	H.264/H.265
Audio	Up to 32 through IP Cameras
Video Outputs	2 Independent HDMI & 2 VGA Mirrors
Hard Drive	
SATA	4 SATA Interface - Supports RAID1 and 5
Disk size	Up to 24TB each disk* Larger capacity disks must be below 104°F environmental temperature.
Video Capacity (Assumes standard bitrates, results may vary depending on video content)	32 Cameras with 96TB Installed (4x24TB) ~40 days with 4K 30FPS constant ~80 days with 4MP 30FPS constant ~160 days with 2MP 30FPS constant
External Interface	
Network	Dual Gigabit Ethernet for Multi-Network
Built in PoE	24 Built in 100/10 PoE Ports
PoE Supply	802.3af/at - 30W maximum per port, total 210W
USB Interface	2 x USB 2.0 (front) and 2 x USB 3.0 (rear)
Alarm In/Out	16 in / 10 out
General	
Smart Features by NVR	16 UMD/8 Smart Intrusion or TraceSearch mode
Smart Feature Limitations	UMD: 16-ch 2MP, 8-ch 4MP, 4-ch 4K Smart Intrusion: 8-ch 2MP, 4-ch 4MP, 2-ch 4K
Power Supply	100 ~ 240 VAC
Temperature/Humidity	14F - 131F @ 10%-90% Humidity
Chassis	2U Rack Mountable (Ears included)
Dimensions & Weight	17.4" x 17" x 3.5" / 12.5lbs without HDDs